



...Simply the right choice

CV1000 Bill Validator

High performance delivered at a value-for your operation and bottom line.

The CONLUX CV1000 delivers high performance to the value conscious operator. Built upon the MEI CONLUX® heritage of market leading bill validators, the CONLUX CV1000 is simple to operate and offers solid reliability.

CV1000 Acceptance Features

Accepts notes from \$1-\$20 at a 95% acceptance rate or greater. 4-way bill acceptance is now offered in the Conlux brand with the CV1000. Sensors for validation are all optical technology and boast dual pellet sensing.

Market your business with coupons! The CV1000 offers more coupon options to operators than previous Conlux validators. Select from four different versions, which include a secure, low cost option.

Merchandising Made Simple

The CV1000 bezel design allows the validator to clear the latest LCD screens being placed on today's vending machines from a distance.

CV1000 bezel LED's are brighter than its predecessor CONLUX validators, helping merchandise your machines.

Keep the 'storefront' open longer with 300 and 500 note cashbox options which are convenient sizes for busy machines. Dual side entry cashbox doors provide drivers easy access to collect cash and are colored in a distinguishable royal blue hue.



CV1000

- Accept \$1-\$20
- 4-way bill acceptance
- 300 or 500 note cashbox
- 24Volt MDB only

CV1000 Bill Validator

Simple Programming.

Enable and disable acceptance at the push of a button. To set the bill denomination acceptance of your choice, simply press the blue button on the back of the validator and feed the bill denominations of your choice. Or a configuration coupon can be used to activate specific denomination control, orientation, and bezel light flashing. The validator can even conveniently remain installed in the machine while configuring the denominations.

Status LED's on the rear of the validator conveniently assist in troubleshooting the CV1000 right in the field. Programming updates to the validator may be done in field with the use of a BPM (bill programming module).



CV1000 Specifications

Acceptance Rate	95% or greater
Bill Insertion	Lengthwise, four-way (face up or down, either direction)
Interfaces	MDB
Power Source	22 to 45 VDC
Power Consumption	Standby: 5 Watts Acceptance: 15 Watts Full Stack Max: 20 Watts
Escrow Supported	
Approximate Shipping Weight	5 lbs (1.6kg)
Environment	Operating Temperature: -15° C to 60° C Storage Temperature: -40° C to 70° C

Model	Part #	Industry Segment
CV1012-U5M	46604	Bottling
CV012-U3M	46603	Bottling
CV1022-U5M	45604	Full-line



MEI Corporate Headquarters
1301 Wilson Drive
West Chester, Pennsylvania 19380
1-610-430-2700
1-800-345-8215
www.meigroup.com