Imbera
Beyond Cooling

EVC04 HC

Establishing a NEW STANDARD in the commercial refrigeration industry.

The new environmentally friendly HC countertop cooler offers high efficiency, low utility costs, and spark-free components that meet Coke requirements.
Comes with a stainless steel top and is ideal for self-checkout areas.

KEY FEATURES

ELECTRONIC TEMPERATURE CONTROLLER
Assures the optimal performance of the cooler, delivering product temperature ideal for consumption.

ECO-FRIENDLY NATURAL REFRIGERANT
New R600 HFC-free refrigerant gas that reduces environmental impact and increases efficiency.

ELECTRONIC FAN MOTORS Enhances performance and efficiency. Uses only a fraction of the energy than industry standard shaded-pole motor requires. Longer useful life fan motor.

LOW MAINTENANCE CONDENSER
Designed to reduce dust & debris accumulation, which significantly reduces service frequency, run time, and guarantees refrigeration system longevity.

HIGH EFFICIENCY GLASS DOOR
"Low-e" double panel argon gas filled glass-pack with an extruded insulated plastic frame, making this door the most energy efficient in its category.

LED PERIMETER LIGHTING
All our NGD doors come standard with a 220+ LUX of LED output, a 50% increase in brightness from our previous 150 LUX LED models, while maintaining extremely low energy consumption levels.

CYCLOPENTANE INSULATION
Eco-friendly, recyclable and high efficiency cabinet insulation.

ENERGY STAR 4.0

c UL us LISTED
COMMERCIAL REFRIGERATOR AND/OR FREEZER
9Z42

CLASSIFIED UL EPH
NSF/ANSI 7 COMMERCIAL REFRIGERATOR AND/OR FREEZER
20YY

EVC04 HC



TOP VIEW



FRONT VIEW



SIDE VIEW

TECHNICAL SPECIFICATIONS

External Dimensions	H:	32 3/4″	830 mm
	W:	21 1/4″	540 mm
	D:	22 5/8″	576 mm
Internal Dimensions	H:	28 5/8″	726 mm
	W:	18″	458 mm
	D:	18 3/4″	476 mm
Weight	Gross:	114.6 lb	52.0 kg
	Crated:	123.5 lb	56.0 kg
Volume		3.9 ft³	111.0 lts
Capacity	53′:		160
Doors	1		
Shelves	2		
20 oz bottle capacity	Total:		60
	Facings:		6

REFRIGERATION DATA

Energy Consumption (kWh/24h)	0.783
Refrigerant R600 (oz)	1.06
Compressor (hp)	1/8
Evaporator	Dynamic
Temp range	32°F to 44.6°F

ELECTRICAL DATA

Amps (A)	2.0	
Volts (V)	115	
Frequency (Hz)	60	
Lighting	LEDs	
Cord Lenght	118″	3000 mm
Plug type	NEMA 5-15P	

IMBERA USA L.L.C.
245 TownPark Drive Suite 145
Kennesaw, GA 30144
www.imberacooling.com

* Energy consumption based on ANSI/ASHRAE Standard 72-2005.

BMAD System (*Low maintenance high performance*).
Dimensions rounded up to the nearest inch or milimeter.
Specifications subject to change without notice.