Imbera
Beyond Cooling

VR06 HC

Establishing a NEW STANDARD in the commercial refrigeration industry.

The new environmentally friendly HC small size countertop cooler offers high efficiency, low utility costs, and spark-free components that meet Coke requirements, providing great functionality for any size space.

KEY FEATURES

ELECTRONIC TEMPERATURE CONTROLLER
Assures the optimal performance of the cooler, delivering product temperature ideal for consumption.

ECO-FRIENDLY NATURAL REFRIGERANT
New R600 HFC-free refrigerant gas that reduces environmental impact and increases efficiency.

ELECTRONIC FAN MOTORS
Enhances performance and efficiency. Uses only a fraction of the energy and offers longer life expectancy than industry standard shaded-pole motors.

LOW MAINTENANCE CONDENSER
Designed to reduce dust & debris accumulation, which significantly reduces service frequency, run time, and guarantees refrigeration system longevity.

HIGH EFFICIENCY NGD DOOR
Equipped with our Next Generation Door (NGD), a sleek and innovative design with a self-closing hinge and double glass panels with low-e film that reduce condensation and increase overall consumer appeal.

LED LIGHTING SYSTEM
All our NGD doors come standard with a 220 + LUX of LED output, a 50% increase in brightness from our previous 150 LUX LED models, while maintaining extremely low energy consumption levels.

CFC AND HFC CYCLOPENTANE FOAM
Eco-friendly, recyclable and high efficiency cabinet insulation.

ENERGY STAR

c UL us LISTED
COMMERCIAL REFRIGERATOR AND/OR FREEZER
9Z42

CLASSIFIED UL EPH
NSF/ANSI 7 COMMERCIAL REFRIGERATOR AND/OR FREEZER
20YY

VR06 HC



TOP VIEW



FRONT VIEW



SIDE VIEW

TECHNICAL SPECIFICATIONS

External Dimensions	H:	36″	914 mm
	W:	21 1/2″	545 mm
	D:	25 3/8″	646 mm
Internal Dimensions	H:	31 3/4″	807 mm
	W:	18″	456 mm
	D:	21 3/4″	554 mm
Weight	Gross:	132.3 lb	60.0 kg
	Crated:	136.9 lb	62.1 kg
Volume		5.1 ft³	144.4 lts
Truck load	53′:		160
Doors	1		
Shelves	3		
20 oz bottle capacity	Total:		84
	Front:		6

REFRIGERATION DATA

Energy Consumption (kWh/24h)	0.911*
Refrigerant R600 (oz)	1.20
Compressor (W)	240
Evaporator	Dynamic
Temp range	32°F to 44.6°F

ELECTRICAL DATA

Amps (A)	2.2	
Volts (V)	115	
Frequency (Hz)	60	
Lighting	LEDs	
Cord Lenght	118″	3000 mm
Plug type	NEMA 5-15P	

IMBERA USA L.L.C.
245 TownPark Drive Suite 145
Kennesaw, GA 30144
www.imberacooling.com

* Energy consumption based on ANSI/ASHRAE 72-2005.

BMAD System (*Low maintenance high performance*).
Dimensions rounded up to the nearest inch or millimeter.
Specifications subject to change without notice.